

GENERAL SAFETY

MOST IMPORTANT –RISK ASSESS

Before you commence any work at your chosen work area, you should undertake some preliminary hazard identification and risk control precautions. Ideally more than one person should do this.

This is undertaken by:

Physically inspecting the work site.
Reviewing the best way / job steps required to complete the task.
Reviewing the Safe Work information supplied with the equipment.
Reviewing other reference documentation and expert advice.

The hazard identification and control process steps are defined as:

Identify the hazards (e.g. 240v power drill use around wet areas)
Assess the Risk (multiple earth paths – possible electrocution)
Select the control measure (e.g. dry the area, use an RCD, use a cordless drill etc)
Re-assess the risk. (risk of electrocution now negligible) This is undertaken to ensure that the risk control measures adopted have not introduced any new risks to the work area.

HELP

If the unit does not operate or you are unhappy with its performance, return it to our Hire depot for exchange or call for assistance. Do not attempt repairs yourself.
Refer to your hire contract for contact information.

SAFETY DO'S

DO take the time to read this User Guide and any other safety information provided (e.g. Decals, manufacturers instruction booklets), completely before operating any equipment.
DO satisfy yourself that you have the correct machine for the job and that you are aware how to safely operate it.
DO ensure you fully understand and are familiar with its operation including emergency shut off procedures.
DO ensure that the equipment is assembled and used according to the manufactures and hires instruction.
DO check controls and any other safety devices.
DO make sure you hold a posses a Certificate of Competency issued by the Regulatory Authority where required by particular equipment.
DO where possible operate in a clear work space free from non essential persons.
DO ensure that you have secure footing and clear access to the work area.
DO ensure that the work area is well lit with all aspects of the job easily seen.
DO ensure correct lifting techniques are used when using or transporting any machine or equipment.

SAFETY DONT'S

DO NOT operate any equipment if you are tired or suffering a medical condition, or if under the influence of Alcohol or drugs which, may cause drowsiness.
DO NOT hurry or take risks.
DO NOT operate equipment without guards correctly fitted.
DO NOT operate faulty equipment. If in doubt call your nearest Hire Depot.

Aluminum Trestle Safety Instructions

Read and understand these instructions before using this equipment.

Safety Instructions for this Equipment

- Trestle / ladder must be in the fully open position before work can commence
- Make sure all four legs are firmly on the ground and that the trestle / ladder is stable before climbing
- Leg levelers are designed to level the trestle / ladder and can be used to gain extra height.-
- Platforms must be kept clear and free of objects or tools that could trip or injure a person on or below the working platform
- A maximum span of 5.5 meters is accepted if two aluminum planks are clamped together with a "Tommy Tucker Plank Clamp"
- Allow no less than 250mm overhang of each end when plank is placed over the rung of the trestle.
- Always test ground for hardness. If an 80kg man standing on the balls of his feet sinks in, you will need timber packers at least 250mm by 300mm in length placed under the feet of the trestle.
- **The trestle safety system must be used when there is a chance of falling more than 2 meters.**

Please read this guide carefully prior to operating equipment.

Safety Equipment

The following protective equipment **MUST** be worn when using this equipment:

- Leather boots
- Suitable clothing.

General Safety

- Do not use machinery if you feel tired or under the influence of alcohol or drugs.
- Check controls for proper response. Shut down the machine if a fault is detected.
- Do not wipe plastic parts with solvents, such as petrol, thinner, alcohol and ammonia, as they will damage and crack plastic parts.
- Wipe parts with a soft cloth lightly dampened with soapy water.
- Always use the right tools. Never force a tool or attachment to do a job for which it was not designed. When using attachments, ensure they are fitted correctly and practice the operation before beginning work. Always use recommended accessories only.
- Always keep guards in place and in working order.
- Do not wear loose clothing, gloves, neckties, rings, bracelets or other jewelry which may get caught in the moving parts.
- Do not overreach. Ensure proper footing and balance when working with the tool.
- Always keep the work area well lighted.
- Never permit children, other people or animals to loiter near the work area.

- Do not fool around while operating, always keep the machine under control.
- Never leave a machine running while unattended.
- Do not use or continue to use faulty or damaged equipment.
- Check the condition of the machine at the end of each day and report any damage or defects.
- **REMEMBER: In the event of death, serious injury or a dangerous occurrence you must notify WHSQ 1300 369 915**

For further information or if in doubt over the use of this equipment, contact the supplier and ask for Instructions.

Lockyer Hire Service
438 Warwick Rd, Yamanto, Qld 4305
Ph. 07 3288 0202

PERSONAL PROTECTION EQUIPMENT

- To be used with all equipment as required.



WHATEVER YOU NEED TO GET THE JOB DONE...JUST ASK US !

This operating brochure is intended as a guide only for the safe operation of the equipment. In no way does this brochure override license requirements. If you are unsure about any aspect of this guide or if you are in doubt about its proper use please feel free to contact your nearest depot. Our staff are on hand to answer any question you may have regarding the safe operation of this equipment.