GENERAL SAFETY

MOST IMPORTANT -RISK ASSESS

Before you commence any work at your chosen work area, you should undertake some preliminary hazard identification and risk control precautions. Ideally more than one person should do this. This is undertaken by:

Physically inspecting the work site.

Reviewing the best way / job steps required to complete the task. Reviewing the Safe Work information supplied with the equipment. Reviewing other reference documentation and expert advice.

The hazard identification and control process steps are defined as:

Identify the hazards (e.g. 240v power drill use around wet areas) Assess the Risk (multiple earth paths – possible electrocution) Select the control measure (e.g. dries the area, use an RCD, use a cordless drill etc.)

Re-assess the risk. (risk of electrocution now negligible) This is undertaken to ensure to ensure that the risk control measures adopted have not introduced any new risks to the work area.

HELP

If the unit does not operate or you are unhappy with its performance, return it to our Hire depot for exchange or call for assistance. Do not attempt repairs yourself. Refer to your hire contract for contact information.

SAFETY DO'S

DO take the time to read this User Guide and any other safety information provided (e.g. Decals, manufacturers instruction booklets), completely before operating any equipment. DO satisfy yourself that you have the correct machine for the job and that you are aware how to safely operate it.

DO ensure you fully understand and are familiar with its operation including emergency shut off procedures.

 ${\rm DO}$ ensure that the equipment is assembled and used according to the manufactures and hires instruction.

DO check controls and any other safety devises.

DO make sure you hold a possess a Certificate of Competency issued by the Regulatory Authority where required by particular equipment.

DO where possible operate in a clear work space free from nonessential persons.

 $\ensuremath{\text{DO}}$ ensure that you have secure footing and clear access to the work area.

 $\ensuremath{\text{DO}}$ ensure that the work area is well lit with all aspects of the job easily seen.

DO ensure correct lifting techniques are used when using or transporting any machine or equipment.

SAFETY DONT"S

DO NOT operate any equipment if you are tired or suffering a medical condition, or if under the influence of Alcohol or drugs which, may cause drowsiness.

DO NOT hurry or take risks.

DO NOT operate equipment without guards correctly fitted. **DO NOT** operate faulty equipment. If in doubt call your nearest Hire Depot.

Electric Demolition Saw Safety Instructions

Read and understand these instructions before using this equipment.

Safety Instructions for this Equipment

- Always hold with two hands when the engine is running. Place your left hand on the front handle bar and your right hand on the rear handle and throttle trigger. This applies to left-handed users also.
- Stop the engine before putting down or carrying this machine. Ensure the cutting wheel has come to a complete stop. When carrying grip the front handle and place the exhaust muffler at the side away from the body. Avoid touching the muffler as It gets hot.
- Dust may collect on the power head, especially around the carburetor and may collect petrol resulting in danger of fire. Clean dust from power head regularly.
- Do not drop start. Start on firm ground or other solid surface. Never attempt to start when the cutting wheel is in a cut. Do not allow the starter grip to snap back into position. Guide starter rope slowly back into position. Never start with the starting-throttle lock engaged.
- Avoid standing in direct line with the blade.
- Do not use on flammable grounds. Direct sparks away from the operator or any flammable surroundings.
- Adjust the wheel guard to ensure the user is not endangered by particles of the material being cut, sparks or pieces of damaged wheels; either directly or by ricochet.
- Do not cut into any pipe drum or other container without first ensuring that it does not contain roller tile or flammable substance.
- Always maintain a firm foothold. Do not use on a ladder or any other insecure support. Do not cut above shoulder height. Begin cutting and continue at full throttle. Release the pressure as you reach the end of the cut.
- Ensure an adequate supply of water on both sides of the blade. This will ensure there is no blade damage and will reduce dust.

- Ensure water does not spray on the motor.
 Do not allow waste water to accumulate underfoot
- Do not anow waste water to accumulate underiod

The following protective equipment MUST be worn when using this equipment.

- Goggles or face shield.
- Ear muffs or ear plugs
- Dust mask if in confined space
- Leather gloves
- Hard hat if falling trees in work area
- Leather boots with steel caps.
- Close fitting long sleeve shirt and long pants

Electrical Safety

- Never use the tool in damp or wet places, and never expose them to rain unless specifically designed for that purpose.
- Do not handle the plug or unit with wet hands.
- Do not use the tool in the presence of flammable liquids or gases unless specifically designed for that purpose.
- Never carry tool from the cord or yank it to disconnect from receptacle. Keep cord from heat, oil and sharp edges. Never use the machine if the cord is cut, cracked, worn or damaged.
- Never risk unintentional starting when plugging in the tool. Confirm the switch is in the OFF position before inserting the power plug in the receptacle.
- Do not touch movable parts or accessories unless the power source has been turned off.
- Always disconnect the tool before changing accessories.
- When not in use, tools should be stored, place out of reach of children.

Never lock switches in 'ON' position with tape, wire or by any other means

General Safety

- Do not use machinery if you feel tired or under the influence of alcohol or drugs.
- Check controls for proper response. Shut down the machine if a fault is detected.
- Do not wipe plastic parts with solvents, such as petrol, thinner, alcohol and ammonia, as they will damage and crack plastic parts.

- Wipe parts with a soft cloth lightly dampened with soapy water.
- Always use the right tools. Never force a tool or attachment to do a job for which it was not designed. When using attachments, ensure they are fitted correctly and practice the operation before beginning work. Always use recommended accessories only.
- Always keep guards in place and in working order.
- Do not wear loose clothing, gloves, neckties, rings, bracelets or other jewelry which may get caught in the moving parts.
- Do not overreach. Ensure proper footing and balance when working with the tool.
- Always keep the work area well lighted.
- Never permit children, other people or animals to loiter near the work area.
- Do not fool around while operating; always keep the machine under control.

REMEMBER: In the event of death, serious injury or a dangerous occurrence you must notify WHSQ 1300 369 915. For further Information or if in doubt over the use of this equipment, contact the supplier and ask for Instructions.

Lockyer Hire Service 438 Warwick Rd, Yamanto, Qld 4305 Ph. 07 3288 0202

PERSONAL PROTECTION EQUIPMENT
 To be used with all equipment as required.



WHATEVER YOU NEED TO GET THE JOB DONE...JUST ASK US !

This operating brochure is intended as a guide only for the safe operation of the equipment. In no way does this brochure override license requirements. If you are unsure about any aspect of this guide or if you are in doubt about its proper use please feel free to contact your nearest depot. Our staff are on hand to answer any question you may have regarding the safe operation of this equipment.